

Red Laser Diode

Part No: LD-640-15A-40-B-2



Features

- ※ Wavelength: $\lambda = 640\text{nm}$ (Type)
- ※ Threshold current: $I_{th} = 110\text{mA}$ (Type)
- ※ Output optical power: 150mW
- ※ Package: T0-18 ($\Phi 5.6\text{mm}$)

Applications

- ※ Industrial Use

Absolute Maximum Rating at $T_c = 25^\circ\text{C}$

Items	Symbols	Values	Unit
Optical Output Power	P_o (CW)	150	mW
Laser Diode Reverse Voltage	V_r	2	V
Operating Temperature	T_{opr}	$-10 \sim +40$	$^\circ\text{C}$
Storage Temperature	T_{stg}	$-40 \sim +80$	$^\circ\text{C}$

Electrical and Optical Characteristics at $T_c = 25^\circ\text{C}$

Items	Symbols	Min	Type	Max.	Unit	Condition
Optical Output Power	P_o	-	150	-	mW	CW
Threshold Current	I_{th}	-	110	140	mA	CW
Operating Current	I_{op}	-	280	350	mA	$P_o = 150\text{mW}$
Slope Efficiency	η	-	0.8	1.1	mW/mA	$P_o = 150\text{mW}$
Operating Voltage	V_{op}	-	2.6	3	V	$P_o = 150\text{mW}$
Lasing Wavelength	λ	635	640	645	nm	$P_o = 150\text{mW}$
Beam Divergence	//	8	10	12	$^\circ$	$P_o = 150\text{mW}$
	\perp	14	18	22	$^\circ$	$P_o = 150\text{mW}$
Beam Angle	$\Delta //$	-	-	± 2	$^\circ$	$P_o = 150\text{mW}$
	$\Delta \perp$	-	-	± 2	$^\circ$	$P_o = 150\text{mW}$
Emission Point Accuracy	$\Delta X, \Delta Y, \Delta Z$	-80	-	80		$P_o = 150\text{mW}$

1) Measurement condition: CW

2) Full angle at half maximum.

3) All the above values are measured by OPELUS method.

Red Diode

Package and Electrical connection

