

# Infrared Laser Diode

Part No: LD-980-2A-40-A-2



## Features

- ※ Wavelength:  $\lambda = 980\text{nm}$  (Type)
- ※ Low threshold current:  $I_{th} = 65\text{mA}$  (Type)
- ※ Output optical power: 200mW (CW)
- ※ Package: T0-18 ( $\Phi 5.6\text{mm}$ )

## Applications

- ※ Industrial Use

## Absolute Maximum Rating at $T_c = 25^\circ\text{C}$

Items	Symbols	Values	Unit
Optical Output Power	$P_o$ (CW)	200	mW
	$V_r$ (LD)	2	V
Operating Temperature	$T_{opr}$	$-10 \sim +40$	$^\circ\text{C}$
Storage Temperature	$T_{stg}$	$-40 \sim +80$	$^\circ\text{C}$

## Electrical and Optical Characteristics at $T_c = 25^\circ\text{C}$

Items	Symbols	Min	Type	Max.	Unit	Condition
Threshold Current	$I_{th}$	-	65	105	mA	CW
Operating Current	$I_{op}$	-	320	360	mA	$P_o = 200\text{mW}$
Operating Voltage	$V_{op}$	-	1.6	2.1	V	$P_o = 200\text{mW}$
Slope Efficiency	$\eta$	0.5	0.8	-	mW/mA	$P_o = 200\text{mW}$
Lasing Wavelength	$\lambda$	965	980	995	nm	$P_o = 200\text{mW}$
Beam Divergence	//	8	12	14	$^\circ$	$P_o = 200\text{mW}$
	$\perp$	30	35	40	$^\circ$	$P_o = 200\text{mW}$
Beam Angle	$\Delta //$	-	-	$\pm 3$	$^\circ$	$P_o = 200\text{mW}$
	$\Delta \perp$	-	-	$\pm 3$	$^\circ$	$P_o = 200\text{mW}$
Emission Point Accuracy	$\Delta X \Delta Y \Delta Z$	-80	-	80	$\mu\text{m}$	-

1) Measurement condition: CW

2) Full angle at half maximum.

3) All the above values are measured by OPELUS method.

# Infrared Diode

## Package and Electrical connection

