

Infrared Laser Diode

Part No: LD-850-05-60-N-2



Features

- ※ Wavelength: $\lambda = 850\text{nm}$ (Type)
- ※ Output optical power: 10mW
- ※ Package: T0-18 ($\Phi 5.6\text{mm}$)

Applications

- ※ Industrial Use

Absolute Maximum Rating at $T_c=25^\circ\text{C}$

Items	Symbols	Values	Unit
Optical Output Power	P_o (CW)	10	mW
	V_r (LD)	2	V
Laser Diode Reverse Voltage	V_r (PD)	30	V
Operating Temperature	T_{opr}	$-10 \sim +60$	$^\circ\text{C}$
Storage Temperature	T_{stg}	$-40 \sim +85$	$^\circ\text{C}$

Electrical and Optical Characteristics at $T_c=25^\circ\text{C}$

Items	Symbols	Min	Type	Max.	Unit	Condition
Optical Output Power	P_o	-	-	12	mW	CW
Threshold Current	I_{th}	-	10	20	mA	CW
Operating Current	I_{op}	-	25	35	mA	$P_o=10\text{mW}$
Slope Efficiency	η	-	0.7	0.9	mW/mA	$P_o=10\text{mW}$
Operating Voltage	V_{op}	-	2	2.3	V	$P_o=10\text{mW}$
Monitor Current	I_m	-	0.2	-	mA	$P_o=10\text{mW}$
Lasing Wavelength	λ	840	850	860	nm	$P_o=10\text{mW}$
Beam Divergence	//	-	9	-	$^\circ$	$P_o=10\text{mW}$
	\perp	-	32	-	$^\circ$	$P_o=10\text{mW}$
Beam Angle	$\Delta //$	-	-	± 2	$^\circ$	$P_o=10\text{mW}$
	$\Delta \perp$	-	-	± 2	$^\circ$	$P_o=10\text{mW}$
Emission Point Accuracy	$\Delta X \Delta Y \Delta Z$	-80	-	80	μm	-

- 1) Measurement condition: CW
- 2) Full angle at half maximum.
- 3) All the above values are measured by OPELUS method.

Infrared Diode

Package and Electrical connection

