

# Red Laser Diode

Part No: LD-635-05-50-N-2



## Features

- ※ Wavelength:  $\lambda = 635\text{nm}$  (Type)
- ※ Threshold current:  $I_{th} = 30\text{mA}$  (Type)
- ※ Output optical power: 5mW
- ※ Package: T0-18 ( $\Phi 5.6\text{mm}$ )

## Applications

- ※ Industrial Use

## Absolute Maximum Rating at $T_c = 25^\circ\text{C}$

Items	Symbols	Values	Unit
Optical Output Power	$P_o$ (CW)	6	mW
	$V_r$ (LD)	2	V
Laser Diode Reverse Voltage	$V_r$ (PD)	30	V
Operating Temperature	$T_{opr}$	$-10 \sim +50$	$^\circ\text{C}$
Storage Temperature	$T_{stg}$	$-40 \sim +85$	$^\circ\text{C}$

## Electrical and Optical Characteristics at $T_c = 25^\circ\text{C}$

Items	Symbols	Min	Type	Max.	Unit	Condition
Optical Output Power	$P_o$	-	5	-	mW	CW
Threshold Current	$I_{th}$	-	30	40	mA	CW
Operating Current	$I_{op}$	-	34	50	mA	$P_o = 5\text{mW}$
Slope Efficiency	$\eta$	-	0.2	0.3	mW/mA	$P_o = 5\text{mW}$
Operating Voltage	$V_{op}$	-	2.2	2.7	V	$P_o = 5\text{mW}$
Monitor Current	$I_m$	0.1	0.15	0.5	mA	$P_o = 5\text{mW}$
Lasing Wavelength	$\lambda$	630	637	640	nm	$P_o = 5\text{mW}$
Beam Divergence	//	6	8	12	$^\circ$	$P_o = 5\text{mW}$
	$\perp$	28	34	40	$^\circ$	$P_o = 5\text{mW}$
Beam Angle	$\Delta //$	-	-	$\pm 2$	$^\circ$	$P_o = 5\text{mW}$
	$\Delta \perp$	-	-	$\pm 3$	$^\circ$	$P_o = 5\text{mW}$
Emission Point Accuracy	$\Delta X \Delta Y \Delta Z$	-60	-	60	$\mu\text{m}$	$P_o = 5\text{mW}$

- 1) Measurement condition: CW
- 2) Full angle at half maximum.
- 3) All the above values are measured by OPELUS method.

# Red Laser Diode

## Package and Electrical connection

